

BACK TO BACK



Sample Part Number	ARMMDBBS-	A	L	37	T	2	8	E	1	36-	10
Series	ARMMDBBS: Back to Back Shell Type Micro-D Connector Series										
Shell Material	A: Aluminum SS: Stainless Steel										
Insulator Material	L: LCP 30% Glass-Filled Liquid Crystal Polymer P: PPS 40% Glass-Filled Polyphenylene Sulfide										
Contact Layout	9, 15, 21, 25, 31, 37, 51-2, 51, 67, 69, 75, 100										
Contact Type	S: Socket (Female) Connector Both Ends P: Pin(Male) Connector Both Ends T: Pin(Male) Connector to Socket (Female) Connector										
Shell Finish Type	1: Electroless Nickel 2: Cadmium 3: Chem Film 4: Gold 5: Black Anodize 6: Silver 7: Passivated (Only Stainless Steel)										
Wire Gage	4: 24 6: 26 8: 28 0: 30										
Wire Standard	K: M22759/11 L: M22759/33 E: NEMA HP3 (M16878/4)										
Colour Code	1: 10 Colour Repeat 2: Color coded per MIL-STD-681, system 1 3: All White 4: All Yellow										
Wire Length	18: 18 inches 24: 24 inches 36: 36 inches & Special Request (For example: 5 inches)										
Hardware Type	10: Jackpost 11: Hex Head Jackscrew 12: Hex Head Jackscrew Extended 13: Slot Head Jackscrew 14: Slot Head Jackscrew Extended 15: Threaded Insert										