



# PRE-WIRED

Sample Part Number	ARMMDPW-	A	P	15	S	1	6	K	1	18-	10
Series	<b>ARMMDPW:</b> Pre-Wired Micro-D Connector Series										
Shell Material	<b>A:</b> Aluminum <b>SS:</b> Stainless Steel										
Insulator Material	<b>L:</b> LCP 30% Glass-Filled Liquid Crystal Polymer <b>P:</b> PPS 40% Glass-Filled Polyphenylene Sulfide										
Contact Layout	<b>9, 15, 21, 25, 31, 37, 51-2, 51, 67, 69, 75, 100</b>										
Contact Type	<b>S:</b> Socket (Female) <b>P:</b> Pin (Male)										
Shell Finish Type	<b>1:</b> Electroless Nickel <b>2:</b> Cadmium <b>3:</b> Chem Film <b>4:</b> Gold <b>5:</b> Black Anodize <b>6:</b> Silver <b>7:</b> Passivated (Only Stainless Steel)										
Wire Gage	<b>4:</b> 24 <b>6:</b> 26 <b>8:</b> 28 <b>0:</b> 30										
Wire Standard	<b>K:</b> M22759/11 <b>L:</b> M22759/33 <b>E:</b> NEMA HP3(M16878/4)										
Colour Code	<b>1:</b> 10 Colour Repeat <b>2:</b> Color coded per MIL-STD-681, system 1 <b>3:</b> All White <b>4:</b> All Yellow										
Wire Length	<b>18:</b> 18 inches <b>24:</b> 24 inches <b>36:</b> 36 inches & Special Request (For example: 5 inches)										
Hardware Type	<b>10:</b> Jackpost <b>11:</b> Hex Head Jackscrew <b>12:</b> Hex Head Jackscrew Extended <b>13:</b> Slot Head Jackscrew <b>14:</b> Slot Head Jackscrew Extended <b>15:</b> Threaded Insert										